



Humidity Conditioning Cabinets



This units function as variable humidity, temperature humidity, environmental, climatic or conditioning cabinets. Their reliability, ease of operation and robust construction has led to their use worldwide in all major sectors of industry. Temperature and humidity testing and product conditioning is of vital importance to ensure the product is researched, developed and manufactured to a standard guaranteed to survive the environment for which it is designed.

★ Features

- ✓ Step-up-step-down programming facility
- ✓ Full digital display
- ✓ Keypad control panel
- ✓ Humidity generator/condenser unit supplied

📋 Standards

ASTM B1117, BS 3900-F12, DIN 50021, Ford EU B 153-2, GM 9540 P, ISO 7253, JIS K 5622-7, Nissan M0007, Swaat & Mastmaasis Honda 5100Z, Toyota TSH 1555G, Unichem 692 & 741, VDA 624-415, VW-1210-C

⚙️ Technical Specifications

Dimensions 100 litre (LxWxH)	1020 mm x 730 mm x 780 mm / 40.1 inch x 28.7 inch x 30.7 inch
Dimensions 200 litre (LxWxH)	1000 mm x 830 mm x 1040 mm / 39.3 inch x 32.6 inch x 40.9 inch
Dimensions 450 litre (LxWxH)	1330 mm x 1020 mm x 1120 mm / 52.3 inch x 40.1 inch x 44.0 inch
Dimensions 750 litre (LxWxH)	1730 mm x 1290 mm x 1370 mm / 68.1 inch x 50.7 inch x 53.9 inch
Dimensions 1000 litre (LxWxH)	1950 mm x 1350 mm x 1380 mm / 76.7 inch x 53.1 inch x 54.3 inch
Dimensions 2000 litre (LxWxH)	2760 mm x 1360 mm x 1650 mm / 108.6 inch x 53.5 inch x 64.9 inch
Power Supply	230 V 50/60 Hz single phase, other voltages on request

📄 Ordering Information

Visit www.cw-spec.com for ordering information, or contact your local representative.

Your C&W direct contact nr: +44 (0) 2039 3635 65.



Scope of supply

Humidity Conditioning cabinet, installation kit, set of collection vessels (2 funnel, 2 cylinder), adapter for pipe, corrosion handbook



Calibration Certificate Included



◀ Ventilatoren



◀ Wheels
makes it easy to move