



MX40-32A-P-S-PP

3.000 - 4.000 l/h Discs, cartridges, bag

Typical applications
Plating and process industry

Features

- Service friendly, ideal cleaning access height
- Magnetic drive pump
- Filter chamber with welded bottom (no seal)
- Discs (thin/thick paper, cloth), cartridges or pleated bag
- All PP construction
- Max. temperature PP 80°C
- Bottom-out or top-out model
- Choice of slurry tank for carbon treatment, mixing and priming
- Unions for rigid piping (PP or CPVC sockets)
- Standard with 3 phase motor, thermal overload switch, lead without plug, pressure gauge, air release and drain valve

Options

- Hose connection
- Contact manometer
- Single open end cartridges



M15-31A-K-PP

Filter Systems series 3

www.hendor.com

Pump	l/h	kW	Union (d/DN) In Out	Hose In Out	Type	Chamber	Medium	Slurrytank	Material
Magnetic drive	3000	0,18	32/25 25/20	1 1/4" 1"	M15 MX40	31A	K/P		PP-EPDM
	4000	0,18				32A			
						31 32	K/P/D		
Selection:					MX40	32A	P	S	PP

K = cartridges

Qty x L
31(A)-K = 3 x 10"
32(A)-K = 3 x 20"

P = discs

Qty	OD/ID	m ²
31-P = 37 x 136/32	0,5	
32-P = 69 x 136/32	1,0	
31A-P = 32 x 136/32	0,4	
32A-P = 65 x 136/32	0,9	

D = pleated bag

L	m ²
31-D = 10"	0,4
32-D = 20"	0,7