

## Dino-Lite AM4013MTL

Dino-Lite X Pro with aluminum alloy housing and long working distance and Microtouch. The aluminum housing offers enhanced protection and durability and has the best look and feel. The enhanced color sensor provides superior color rendering and improved low light imaging.



### Technical data

|                       |   |
|-----------------------|---|
| <b>Model</b>          | <b>AM4013MTL</b>                                  |
| Resolution            | 1,3 megapixel (1280x1024 pixels)                  |
| Magnification         | 10x ~ 92X   |
| Interface             | USB 2.0, High speed USB transmission              |
| Nr. of LED's          | 8   |
| LED on/off switchable | √   |
| LED color             | White   |
| Material              | Full aluminum alloy body                          |
| Microtouch            | √   |
| Output                | Picture, video and time-lapsed video              |
| Video Frame Rate      | up to 30 frames-per-second, 15fps at 1.3M         |
| Measurement           | √<br>(line, radius, circle, 3-point circle, etc.) |
| Calibration           | √   |
| Filter/Diffuser       | -   |
| Compatibility         | Windows XP, Vista, 7 and recent MAC OS            |
| Software (included)   | Windows: DinoCapture, Mac: DinoXcope              |
| Special               | best model for repair, rework or assembly tasks   |