



Spring Loaded Roller

SP3600

Datasheet

Product Description:

The Spring Loaded Roller is used to perform objective dust tape tests, as mentioned in ISO 8502-3, and eliminates the human factor. The Spring loaded roller is so designed that it is capable of applying a load of 44,13 N. Iso 8502-3 quantifies the quantity and size of dust particles on surfaces prepared for painting. This test has to be performed just before the paint is applied. The test itself is not included in the delivery

Standards

ISO 8502-3



Application area's Coating/Paint Industry, Galvanise, Construction/building maintenance, Painters, Shipping Industry, Steel Protection.

Features

- Made of Titanium anodised aluminum
- Equal pressure ensured
- Ergonomic design - easy to use
- Almost maintenance-free
- Robust and sturdy

Additional Information:

Dust on blast cleaned surfaces can reduce coating adhesion, leading to premature coating failure and sub-standard coating finish.

Specifications

Dimensions: 100 x 185 x 70 mm
 60 x 185 x 70 mm (when in use)
 Weight: 740 grams
 Rubber hardness wheel: 50 IRHD
 Load: 4,5 kg / 44,13 N.
 Housing: titanium anodised aluminum

Accessories

LD2056 Dust tape test kit
 LD2057 Spare roll of tape

Delivery

- Spring loaded roller
- Sturdy case
- Calibration certificate

Safety Precautions/ Maintenance:

- Always keep the instrument in its case when not in use.
- Though robust in design, this instrument is precision-machined. Never drop it or knock it over
- Clean the instrument with a damp soft cloth. Never use abrasives or solvents.

Disclaimer:

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

reprüfung fineness of grind maatlijheid mateinheit drying time droogtijd Trockenzeit abrasion slijvastheid Abriebfestigkeit inspection accessories / lanz & 'haze' corrosion corrosie Korrosion coating thickness gauges coatingdikte meters Schichtdicken messgeräte flash point vlammpunt Flammpunt the testapparatuur Klimaproefing appearance uiterlijk Erscheinungsbild inspection kits inspectie kits inspectiekoffer elasticity & resistance deformaties weegschalen Waagen surface cleanliness oppervlaktezuiverheid Oberflächenreinheit film application filmapplicatie Filmaufziehgeräte coat